

<b>Power source</b>	<b>Phase</b>	Single-phase
<b>Voltage</b>		~ 230 V
<b>Frequency</b>		50 Hz
<b>Rated Capacity</b>	<b>Cooling</b>	12.5 kW(3.5 - 14.0 kW)
<b>Heating</b>		13.5 kW(3.5 - 16.0 kW)
<b>EER</b>	<b>Cooling</b>	3.50 W
<b>COP</b>	<b>Heating</b>	4.00 W
<b>Sound Pressure Level (High)</b>	<b>Cooling</b>	53 dB(A)
<b>Heating</b>		55 dB(A)
<b>Sound Power Level (High)</b>	<b>Cooling</b>	67 dB(A)
<b>Heating</b>		68 dB(A)
<b>Net Dimensions</b>	<b>Height</b>	998 mm

<b>Width</b>		970 mm
<b>Depth</b>		370 mm
<b>Net Weight</b>		94 kg
		207 lbs
<b>Connection Pipe Diameter</b>	<b>Liquid</b>	6.35×6 mm
	<b>Gas</b>	9.52 × 4, 12.7 × 2 mm
<b>Max Pipe Length</b>	<b>Total</b>	80 m
	<b>Each</b>	25 m
<b>Max Height Difference</b>	<b>Between Outdoor Unit and Each Indoor Units.</b>	15 m
	<b>Between Indoor Units.</b>	10 m
<b>Operation Range</b>	<b>Cooling</b>	-10 to 46 °CDB
	<b>Heating</b>	-15 to 24 °CDB
<b>Refrigerant</b>	<b>Type</b>	R410A
<b>Global Warming Potential</b>		2,088

<b>Charge</b>	4,000 (8.4) g
---------------	---------------